







ASTORI CALL OUT	SIZES	FIELD OF APPLICATION AND MATERIALS	REFERENCE STANDARDS	NOTES	
<b>HEX NUTS</b>					
	PDS10	6-32÷3/8	1100MPa 235°C 35CrMo4	MS21042 NAS1291	reduced hex
	PDS11		1100MPa 425°C A286	MS21043 NAS1291C	
	DS10	3+14	1100MPa 235°C 35CrMo4	LN9338 LN65409	
	DS11		1100MPa 425°C A286	LN9161 LN65410	
	JDS10		1100MPa 235°C 35CrMo4	JN0106 EN3626	
	JDS11		1100MPa 315°C A286	DIN65480 EN3536	
JDS11	1100MPa 425°C A286		EN3196 EN3723 EN3377		
	DRS10	3+12	1100MPa 235°C 35CD4	LN29790	reduced hex with captive washer
	DRS11		1100MPa 425°C A286		
	DRS20		1100MPa 235°C 35CD4		
	DRS21		1100MPa 425°C A286		
	JDRS10		1100MPa 235°C 35CD4	DIN65507 EN2882	
	JDRS11		1100MPa 425°C A286	DIN65508 EN2883 EN3431	
	JDRS20		1100MPa 235°C 35CD4		
	JDRS21		1100MPa 425°C A286	EN3033 EN3034	
	DN20	3+24	900MPa 120°C 25CD4	LN9348	nylon insert
	DN21		900MPa 120°C A286		
	JDN22	3+20	900MPa 120°C 25CD4		
	JDN23		900MPa 120°C A286	DIN65545	
	JDN26	2+24	900MPa 120°C 25CD4	EN4309	
JDN27		900MPa 120°C A286	EN4297		
	DF100	5+14	900MPa 235°C 35CD4		reduced hex, double lock
	DF101		900MPa 425°C A286		
	JDF100	4+24	900MPa 235°C 35CD4	NA0049	
	JDF101		900MPa 425°C A286		
	JDF120	5+24	900MPa 235°C 35CD4	EN3434 ASN-A0225	
JDF121		900MPa 425°C A286			
	DFN30	5+20	1100MPa 120°C 35CD4	MBBN3049	double lock nylon insert
	DFN31		1100MPa 120°C A286		
	JDFN30		1100MPa 120°C 35CD4		
	JDFN31		1100MPa 120°C A286		
	DFN80	5+14	900MPa 120°C 35CD4	MBBN3050	
	DFN81		900MPa 120°C A286		
	JDFN80		900MPa 120°C 35CD4		
	JDFN81		900MPa 120°C A286		
	D010	5+12	900MPa 235°C 35CrMo4	LN29795	ball seat
	D011		900MPa 425°C A286		
	JD020		900MPa 235°C 35CrMo4	EN2647	
	JD021		900MPa 425°C A286	EN3763 JN0098	